ECN-S

COLD WATER HIGH PRESSURE CLEANER - ELECTRIC MOTOR

A compact cold water high pressure cleaner made up of high-quality components complying with DiBO's rigid quality standards. By using a new type radial high pressure pump with 3 ceramic plungers, there are fewer vibrations which results in a very noiseless machine. Suitable for a wide range of cleaning jobs.



STANDARD ACCESSORIES:



10 m high pressure hose (5/16") code : 1.205.520.020



Double stainless steel spray lance with low and high pressure nozzle and rotating quick coupling (only on < 320 bar and < 41 l/min) code: 1.208.630.xxxxx



High pressure gun with swivel code : 1.211.525





Easy storage of electric cable



Height adjustable handle



FEWER VIBRATIONS: radial high pressure pump with 3 ceramic plungers



Option: hose reel with 20 m high pressure hose

TECHNICAL SPECIFICATIONS:

- Automatic start-stop system with a delayed stop (30 s)
- Electric motor with low speed (1450 rpm)
- Radial high pressure pump with 3 ceramic plungers and stainless steel valves
- Pressure gauge
 Coarse particle filter
 ON/OFF switch
- Pressure control valve to adjust the operating pressure
- Detergent injector
- Lightweight and easy to handle high pressure hose of 5/16" (10 m) Powder coated steel frame

Note: Monophase machines work as standard at 1 x 230 V-50 Hz. 3-phase machines work as standard at 3 x 400 V-50 Hz. Other versions on request.

MODELS:

ECN-S											
-5465 4580	TYPE	0		INPUT		Î	7	-	У _А	i	
		bar	I/h	°C	kW	m	1	1	mm	kg	ı
1.105.055	130/10	30 - 130	600	40	3,0 (1 x 230 V - 13 A)- 50 Hz	5	-	-	765 x 530 x 1100	59	040
1.105.280	180/13	30 - 180	780	40	5,2 (3 x 400 V - 8 A)- 50 Hz	5	-	-	765 x 530 x 1100	67	045
1.105.300	210/15	30 - 210	900	40	7,0 (3 x 400 V - 11 A)- 50 Hz	5	-	-	765 x 530 x 1100	72	045
1.105.140	160/20	30 - 160	1200	40	7,0 (3 x 400 V - 11 A)- 50 Hz	5	-	-	765 x 530 x 1100	77	075

ECN-S





RECOMMENDED OPTIONAL ACCESSORIES:

The following special accessories are often requested tools for this type of high pressure cleaners. Please inform us of the desired pressure and flow when placing your order.



Hose reel set with 20 m hose reel code: 1.205.025



High pressure extension hoses with quick release from 10 m up to 25 m, suitable for operating pressures ≤ 250 bar code: 1.205.520.xxxxx



Sewer hoses with nozzle and rotating quick coupling from 10 m up to 25 m, suitable for operating pressures ≤ 200 bar code: 1.238.520.xxxxx



Flexible spray lance with high pressure nozzle, length: 850 mm, operating pressure ≤ 200 bar code: 1.208.828.xxxxx



High pressure grit blasting lance with flat jet nozzle and suction hose suitable for an operating pressure from \leq 250 bar Length : 900 mm

200 mm foam lance with 1 l tank and quick release, suitable for an operating pressure from ≤ 250 bar

code: 1.244.251

code : 1.258.220.xxxxx